

Page 2

COUNTACH TECHNICAL DATA

LP 400

5000 S

Point Gap.....	0.35/0.40 mm	.3 to 5 mm*
Cam Angle.....	48/50°	48/50°
Spark Plugs.....	NGK ABC EV	W5DP
Plug Gap.....	.035 mm	0.35 mm

* This is an electronic ignition car and this setting is the air gap between the trigger teeth and stator and must be set with a non-magnetic feeler ~~gauge~~ *gauge*.

Carburation:

Choke.....	38 mm	36 mm
Aux. Venturi.....	4.50 mm	4.5 mm
Main Jet.....	1.50 mm	1.35 mm
Idling Jet.....	F9/0.50 mm	F9/0.45 mm
Pump Jet.....	0.45 mm	0.35 mm
Emulsifying Tubes.....	F3	F3
Air Correction Jets.....	2.10 mm	2.10 mm
Needle Valve.....	1.75 mm	1.75 mm
Carburetor Exhaust Valve.....	0.70 mm	0.70 mm
Float.....	26 gr.	26 gr.
Float Level.....	8.5 mm	8.5 mm
Pump Stroke.....		16 mm
Starting Jet.....	F5/0.60 mm	F5/0.60 mm

Fluid Levels:

Water Radiator.....	17 lt.	17 lt. (18qt)
Fuel Tank.....	120 lt.	120 lt. (31.5qt)
Engine Oil.....	15.2 lt.	15.3 lt. (18.5qt)
Gearbox Oil.....	3.6 lt.	3.2 lt. (3.35qt)
Differential.....	5 lt.	6.4 lt. (6.7qt)